

RJS Inspector® 3000

Bar Code Verifier by



Features

- Traceable to NIST (National Institute of Standards and Technology)
- Follows the ISO15416 and ANSI X3.182 Bar Code Inspection Method
- Conforms to ISO15426-1 Bar Code Verifier Specification
- Auto-discriminates between all popular symbologies
- Bidirectional scanning
- Multiple scan averaging
- Traditional analysis also provided

```

INSPECTOR 3000
Revision C.01

Single Scan Analysis

USS 3of9
*123456*

Scan Profile Analysis
Reference Decode          A
Decodability              76% A
Symbol Contrast           93% A
Refl (Min)/Refl (Max)    07% A
Edge Contrast (Min)      57% A
MODulation                61% B
Defects                   05% A
Application Compliance    A

Overall Symbol Grade
B/10/660      3.0/10/660

Traditional Analysis

Acceptable
-100% Tol. +100%
-----RAR+++++

Wide/Narrow Ratio        2.3 PASS
Print Contrast signal    92% PASS
Required PCS              75%
Element Refl. (Max)      92% PASS
Reflectance (Min)        07% PASS

Fall/Fail Analysis
Passing Grade Selected   D
Final Results            *PASS*
    
```

Sample printout from the optional thermal printer

The Inspector® 3000 is the lowest price ISO/ANSI verifier from RJS

The Inspector® I-3000 meets the International Organization for Standardization's "Bar Code Print Quality Test Specification (ISO 15416), the American National Standard Institute's "Guideline for Bar Code Quality" (ANSI X3.182-1990), the Uniform Code Council (UCC), and the CEN specifications regarding verification methods and methodology. It also meets International Organization for Standardization's "Bar Code Verifier Conformance Specification" (ISO 15426-1).

This truly unique and powerful instrument is also easy to use. All the popular linear symbologies are supported. Store and print capability, multiple scan averaging and sub-symbology choices are easily accessed through a simple four-button user interface. Analysis information appears immediately on a 32-character alphanumeric liquid crystal display (LCD). A distinct audible tone and a series of five colored LED's indicate whether a bar code is in or out of specification.

In addition to the ISO/ANSI method parameters, traditional analysis parameters are provided on the LCD without a special mode setting.

To accommodate varying label densities, interchangeable wands allow a user to select the appropriate aperture. Two wand choices are available – 6 mil and 10 mil aperture, both with red (660 nm) light wavelength.

If needed, a detailed hard copy printout can be produced from the Inspector® I-3000 using an optional direct thermal printer or inspection data can also be sent to computer using an optional VCI option. This allows verification results to be printed, saved, or transferred to other applications.

This equipment and its documentation were developed to fit into your company's existing ISO 9000/9001/9002 policies and procedures.



Inspector® 3000

Features

ISO/ANSI scan profile test method	Y
Instant "On-Screen" ISO/ANSI grade	Y
ISO/ANSI 10-scan grade averaging	Y
Traditional test method	Y
Special reflectometer mode	Y
Auto-switch Symbologies	Y
Change aperture/wavelength from menu	N
Automatic power off	Y
Data buffer	Y
Command code programming	N
Detail hardcopy printout (optional)	Y

Verification Methods

Parameters determined by ISO/ANSI bar code print quality guidelines and traditional pass/fail criteria. Refer to model matrix below for configurations.

	I-3000
ISO	Y
ANSI	Y
Traditional	Y
Industry Applications:	
SCC Retail	Y
U.P.C Coupon Code	Y
AIAG (Automotive)	Y
LOGMARS (Government)	Y
HIBCC (Health)	Y
SISAC (Serials Coding)	N
CTIA/ABCD (Computer)	N
Bookland (Books)	Y
CCBBA (Blood Bank)	N

Dimensions

Height:	1.9 in. (4.8 cm)
Width:	4.6 in. (11.7 cm)
Length:	7.8 in. (19.8 cm)

Mechanical

Weight:	16 ounces (454 g)
Power:	4 AA NiCad batteries and AC Charger
Case:	Acrylonitrile Butadiene Styrene (ABS)
Beeper:	Audible tones indicate an audible pass/fail and low battery
Display:	4 line X 8 character LCD
Keypad:	4-button, on, select, enter, print
LEDs:	5 LEDs (two red, one yellow, and two green)

Environmental

Operating Temperature:	32 to 122° F (0 to 50° C)
Storage Temperature:	14 to 158° F (-20 to 70°C)
Relative Humidity:	5% to 95% Non-condensing

Optical:

When ordering Inspector 3000 Series verifiers, choose the applicable aperture size

Test Aperture:	6 or 10 mil
Wavelegth:	Visible: 660nm

Symbologies:

EAN/UPC with addenda, Code 39, Interleaved 2 of 5, Codabar, Code 128, Regular 2 of 5 (Discrete/Industrial 2 of 5)

Safety/Regulatory:

FCC Class A, CE Certified



Inspector is a registered trademark of RJS Technologies, Inc. in the United States and/or other countries.

