

Bar Code Inspection Report Printer

BAR CODE VERIFIER

BY 



Sample printout

```

Inspector 5000L
Version 1.108

On 03-24-22 @ 16:54:24
Cont. Scan Analysis

#Decodes 008/008
%Decodes 100%

Interleaved 2 of 5
01928374

Scan Profile Analysis
Reference Decode.....4.0/A
Decodability.....90%...4.0/A
Application Compliance.....4.0/A

Acceptable.....PASS

Traditional Analysis

-100% Tol. +100%
-----A+++++++

Wide/Narrow Ratio.....2.4 PASS

Pass/Fail Analysis
Passing Grade Selected.....1.5/C
Final Results.....*PASS*
  
```



BAR CODE VERIFIER BY RJS

Bar Code Inspection Report Printer

OPTIONAL ACCESSORIES

RJS Direct Thermal Paper
P/N: RJS-Paper-TP140A-2



Dimensions

Height:	5.93" (150.7 mm)
Width:	6.98" (177.5 mm)
Length:	8.69" (220.8 mm)
Weight:	2.98 lbs (1.35 kg)

Electrical

Type:	AC to DC power supply
Input:	100-240VAC; 50-60 Hz
Output:	24V DC; 2.5A

Interface

Type:	Serial cable
Direct Cable Length:	1 meter

Environmental

Operating Temperature:	40°F/5°C - 105°F/41°C
Storage/Transit Temperature:	-40°F/-40°C - 140°F/60°C
Operating Humidity:	10-90% non-condensing
Storage Humidity:	5-95% non-condensing

Safety/Regulatory

- IEC 60950-1
- IEC 62368-1
- EN55022 Class B
- EN55024
- EN55035
- EN61000-3-2
- EN61000-3-3
- FCC Class B
- ICES-003
- FCC 15.209; 15.247(d)
- IC RSS 247
- EN 300 328
- EN 301 893
- EN 62311
- cTUVus CE Marking
- VCCI
- C-Tick
- S-Mark
- CCC
- CU
- BSMI
- KCC
- SABS
- IN-Metro
- BIS
- NOM

